



Core / material / air gap / AL	<b>E16/5 K2006 or equiv.</b>	
Nominal inductance	<b>LI= 1,55mH ±15%</b>	
maximum transmissible power	<b>6W</b>	
Working frequency	<b>44 - 132 KHz</b>	
Transformation ratio	<b>106 : 60 : 10 : 10</b>	
dielectric strength (50Hz/2s)	<b>Prim-Sec = 4kV/50Hz/2sec.</b>	
Nominal Current		
Design in comp. with standard	<b>EN60950 / EN61558</b>	
Working / storage temperature	<b>-25°C- +120°C</b>	<b>-25°C- +85°C</b>
Miscellaneous	<b>F (DIN 40040)</b>	
leakage inductance	<b>max. 60 µH</b>	

Remarks : a.) marking

Measuring device of L: **W&K 3260A**

Measuring conditions of L: **50mV/10kHz/22,5°C**

Measured quantity	Unit	No. 1	No. 2	No. 3	No. 4	No. 5

Responsible person: <b>Uwe Dickhut</b>	Date: <b>18.10.2006</b>	Design regulation no.: <b>063.932</b>	Index: <b>01</b>
---	----------------------------	--	---------------------

**PLEASE GIVE US YOUR WRITTEN RELEASE**

Date Signature